



TVS-4050WK Digital Wireless IP DVR System

The TVS-4050WK is a wireless turn-key solution for multi-channel wireless video monitoring.

FEATURES

- Fully-wireless system
- 4-channel wireless, 3-channel Network Digital Video Recorder
- Very simple, user-friendly System
- Real-time video surveillance
- High-quality Display and Recording (120 F.P.S. NTSC/100 F.P.S. PAL)
- MPEG-4 Hardware Compression
- Multiple Camera Display for Live Viewing or Playback
- Real-time Monitoring, Playback, and Configuration through the Network
- Support Remote Controller

APPLICATIONS

- Business Districts
- Resorts/Hotels
- Perimeter Security
- Retail/Lifestyle Centers
- Executive Protection Services
- Warehouses/Manufacturing
- High School/College Campuses
- Entertainment/Sporting Venues
- Airports/Seaports/Transportation Centers





	FUNCTION	SPECIFICATION
TVS-4050WK Digital Wireless IP DVR System 4 Ch. Wireless 3 Ch. Analog	Video Input	Wireless 4 Ch. + Wired 3 Ch. (RCA Jack)
	Video Output	2 Ch. (RCA Jack)
	Display Mode	Full-screen, Quad
	Display Resolution	704 x 480 (352 x 240 x 4 Ch.)
	Video REC/PB Speed	Wired Mode: 120 IPS Wireless Mode: 30 IPS
	Video CODEC	MPEG-4
	Simplex/Duplex	Simplex
	Display Speed	4 Ch. Real-time
	REC Mode	Event (Motion), Schedule (Date/Time)
	Play Speed	-64/-32/-16/-8/-4/-2/Still/1/2/4/8/16/32/64
PD-100 Cameras	Frame Advance	Forward, Backward
	Video Record Resolution	Wired Mode: 352 x 240/ch. Wireless Mode: 704 x 480/ch.
	REC File Size	High: 8KB/Normal: 4KB/Low: 2KB
	Event List	Recorder Time/Alarm/Motion/Power/Loss Ch.
	Search Mode	Recorder Event Search, Date/Time Search
	Buzzer	0
	Motion Detection	All Channels
	Image Device	1/3" CCD
	Number of Pixels	(H) 512 x (V) 492
	Scanning System	525 Lines, 60 Fields/Sec.
Network	Horizontal Resolution	420 TV Lines
	S/N Ratio	More than 48dB (AGC off)
	White Balance	Auto White Balance (AWB)
Power	Minimum Illumination	1 Lux (F: 2.0)
	Electronic Shutter	1/60 ~ 1/100,000 Sec.
Adapter	Static	0
	PPPoE	ID/PW
Camera Power Output	Port	Default Value: 80
	HDD	Max: 500GB (Default: 160GB)
Remote Control		Yes
Size		(W) 350mm x (H) 59mm x (D) 250mm
Operation Temp.		5C ~ 40C
Storage Temp.		5C ~ 60C
Operating Humidity		20% ~ 85% RH
Storage Humidity		20% ~ 95% RH
Weight		6.6 lbs./3kg.



*All Specifications are subject to change without notice